

STOPRAY SMART

Easy to process
high-performance glass

AGC

Your Dreams, Our Challenge



Stopray Smart glass products have been developed for exterior applications in facades on all types of commercial buildings.

Stopray Smart 51/33 and Smart 30/20 include a silver layer providing super solar control and thermal insulation.

These products can be used in toughened or non-toughened versions. Furthermore, they are easy to process as no edge-deletion is required⁽¹⁾.

Easy to process high-performance glass

STOPRAY SMART

Benefits

One product: two uses

All Stopray Smart products can be used toughened or non-toughened⁽²⁾. The processor's decision will depend on how the building is specified. The toughened and non-toughened versions deliver the same aesthetics, energy, light and insulation performances. A single product with two uses also means less storage space is required.

Easier to process

It is not necessary to edge-delete⁽¹⁾ the coating, greatly facilitating any subsequent processing of the glass and also yielding a remarkable appearance when used in a structural facade.

Perfect visibility

A low interior light reflection guarantees perfect visibility towards the outside world.

Attractive neutral appearance

Stopray Smart 51/33 has a neutral colour, whereas Stopray Smart 30/20 has an attractive neutral bluish colour. They are both in line with current architectural trends.

Superb thermal insulation

Both boasting a Ug value of 1.1 W/(m² K), Stopray Smart 51/33 and Smart 30/20 guarantee a high level of thermal insulation.

Additional combinations

Stopray Smart 51/33 and Smart 30/20 are used exclusively in insulating glazing. They can both be laminated by the processor⁽⁴⁾.

Technical specifications

STOPRAY SMART

Double glazing 6-16-4 (with 90% argon) ⁽⁵⁾			Stopray Smart 51/33	Stopray Smart 30/20 ⁽²⁾
Coating position			#2	#2
Colour			Neutral	Neutral bluish
Light performance	EN 140	LT (%)	51	30
		LR (%)	26	29
		LR int (%)	18	15
Energy performance		SF (%)	34	21
		EA (%)	31	47
		SC	0.39	0.24
Ug value	EN 673	W/(m².K)	1.1	1.1
Toughenable			YES	YES
Non-toughened			YES	YES
Edge deletion			NO ⁽¹⁾	NO ⁽¹⁾
Bendable			YES	YES
Silkscreen printing			YES ⁽⁶⁾	YES ⁽⁶⁾
Shelf life			9 months ⁽³⁾	9 months ⁽³⁾

⁽¹⁾ Please follow the processing instructions in the "Stopray Smart Processing Guide" and in the "Stopray Smart Sealant Compatibility Guide". Don't hesitate to contact your AGC representative if you have any questions.

⁽²⁾ Due to its high absorption factor (EA = 51%), we recommend always toughening Stopray Smart 30/20.

⁽³⁾ This product can be stored for up to nine months thanks to the coating's high level of chemical resistance.

⁽⁴⁾ Care must be taken to ensure the coating does not come into contact with the PVB.

⁽⁵⁾ Identical values for a 15 or 16 mm spacer.

⁽⁶⁾ Please follow the processing instructions in the "Stopray Smart Processing Guide"



Stopray Smart products are
Cradle to Cradle Certified™ Silver

AGC GLASS EUROPE

UNITED KINGDOM: AGC Glass UK - T +44 1788 53 53 53 - sales.uk@agc.com

OTHER COUNTRIES: AGC Glass Europe - T +32 2 409 30 00 - F +32 2 672 44 62
sales.headquarters@agc.com

AGC Glass Europe has representatives worldwide.
See www.yourglass.com for further addresses.



9001051 EN - 03/22

