CLEARSIGHT LITE COMFORT



See what you get, get what you see

AGC is proud to introduce **Clearsight Lite** and **Clearsight Lite Comfort**, two advanced glazing solutions for commercial refrigeration units that enable shoppers to easily see the products on display without being distracted by annoying reflections. Both sides of the glass feature our anti-reflective coating, which ensures that the products behind the glass are perfectly visible while also delivering excellent light transmission. **Clearsight Lite Comfort** also features our low-e coating, delivering superior thermal insulation while significantly reducing energy losses and costs.

Clearsight Lite and Clearsight Lite Comfort Anti-reflective glass for commercial refrigeration units

What's so special about it?

What does this mean for you?

Superb transparency and optimised visibility with almost no reflection

 Both sides coated with our anti-reflective coating to ensure products on display behind the glass are perfectly visible

Higher light transmission

Delivers greater clarity

Enhanced thermal insulation and maximised energy savings

- Reveals colours and enhances contrast for products on display

Keeps goods cool while consuming less energy

Better colour stability and uniformity when viewed from any angle

Choose Clearsight Lite Comfort for superior thermal insulation
 Better aesthetics and a neutral appearance for products inside the refrigeration unit when viewed from any angle

Mechanical and chemical resistance

Durable coating with excellent resistance to scratching and cleaning

Easy to process

Can be toughened, bent and silkscreen printed

Edge deletion not required

Unlimited shelf life

Five-year warranty

Five-year warranty on the Clearsight Lite and Clearsight Lite Comfort coating



Without Clearsight Lite and Clearsight Lite Comfort



With Clearsight Lite and Clearsight Lite Comfort

Performance

	Clearsight Lite	Clearsight Lite Comfort
GENERAL PRODUCT INFORMATION		
Product description	Double sided anti-reflective glass	Double sided anti-reflective glass plus Low-E coating
Glass substrate	Planibel Clearlite	
Standard sizes (mm)	6000 x 3210*	
Thickness (mm)	4	
Emissivity	0.89/0.89	0.89/0.12
Toughenable	YES	
Bendable	YES	
Ceramic printing	YES	
Mechanical and chemical resistance	Class A (EN 1096-2)	
CE marking	YES	
Shelf life	Unlimited	
SINGLE SHEETS - 4 mm (EN 410)		
Light Reflection	≤ 1%	
Light Transmission	97%	92%
Colour rendering index	99%	99%
Haze (max %)	0.1	0.5
U-value (W/(m².K)) - EN673	5.8	3.6
DGU - 4 mm Clearsight Lite -16 mm Argon	90% - 4 mm Clearsight Lite Comfort (EN 410)	
Light Reflection	2%	
Light Transmission	89%	
U-value (W/(m².K)) - EN673	1.4	
DGU - 4 mm Clearsight Lite Comfort - 16 r	nm Argon 90% - 4 mm Clearsight Lite Comfort (EN 4	410)
Light Reflection	2%	
Light Transmission	85%	
U-value (W/(m².K)) - EN673	1.2	

^{*} For other sizes (2250, 2550, 4500, 5100 x 3210), please contact your sales representative

