Technical specifications

PLANIBEL EASY

	Planibel Easy Clear 4 mm	Planibel Easy Clear 6 mm	Planibel Easy Blue 4 mm	Planibel Easy Blue 6 mm
Light Transmission	84	83	63	53
External Light Reflection	14	14	12	14
Solar Factor (%)	82	81	58	50
Energy Reflection (%)	13	13	11	11
Energy Absorption (%)	6	8	41	52

How does the coating work?







1. Coating is activated by UV light

2. Organic deposits are destroyed

3. Rain washes the dirt away



PLANIBEL EASY CLEAR & PLANIBEL EASY BLUE are available

- On Planibel Clearlite and on Planibel Dark Blue in 4 mm and in 6 mm
- In the following sizes: PLF 6000 x 3210 mm

DLF 2250 x 3210, 2550 x 3210

For more details, refer to AGC's Product Catalogue on www.agc-yourglass.com

AGC Glass Europe
UNITED KINGDOM - AGC Glass UK - T +44 1788 53 53 53 - sales.uk@eu.agc.com
OTHER COUNTRIES - AGC Glass Europe - T +32 2 409 30 00 sales.headquarters@eu.agc.com - AGC Glass Europe has representatives worldwide
See www.agc-yourglass.com for further addresses







Keeping windows and your conservatories clean becomes much easier with Planibel Easy Clear and Planibel Easy Blue. How? It's simple: the special coating applied on the glazing works in two steps by using daylight (5 to 7 days) to destroy organic dirt, followed by rain to remove it. This makes it the perfect choice for conservatories, skylights and windows. Moreover, Planibel Easy Clear and Planibel Easy Blue can be combined in double glazing with other AGC products, such as low-e glass.

As simple as Planibel Easy Clear and Planibel Easy Blue

PLANIRFI FASY **CLEAR AND BLUE**

What's so special about it?

What does this mean for vou?

Special two step easy clean coating — Effortless window cleaning as UV light

activates the coating (even on cloudy days) to break down organic dirt and rain washes it away

water over the surface of the glass

Coating works to evenly spread — Uniform cleaning of glass surface, quick drying action

Neutral appearance — Virtually indistinguishable from standard window glass

High light transmission - Lets in maximum daylight

Pyrolitic coating — Very durable and easy to process for glazing manufacturers

Independently tested to EN1096-5 — Easy clean properties tested and verified by the renowned Fraunhofer Institute for Surface Engineering & Tho, Films IST