

Performance

STRATOBEL STOPRAY LAMISMART 24

Outside pane	Inside pane	Coating position	Colour	Composition	Light performances			Energy performances			U _g Value EN 673	Availability*
					EN 410							
					LT (%)	LR (%)	LR int (%)	SF (%)	AE (%)	SC		
Stopray LamiSmart 24	Planibel Clear	2	Neutral blue	44.1	24	35	28	25	48	0.29	5.6	In stock
Planibel Green	Stopray LamiSmart 24	3	Green	44.1	21	23	35	28	74	0.32	5.6	On request
Planibel Bronze	Stopray LamiSmart 24	3	Bronze	44.1	16	16	35	27	70	0.31	5.6	On request
Planibel Grey	Stopray LamiSmart 24	3	Grey	44.1	15	14	35	27	72	0.31	5.6	On request
Planibel Dark Blue	Stopray LamiSmart 24	3	Dark blue	44.1	18	18	35	28	76	0.32	5.6	On request

* Please always refer to AGC Product Catalogue.



9000461 ENG - 01/16

Stopray
LamiSmart 24

THE FIRST STOPRAY® COATING
TO BE LAMINATED!





Stopray LamiSmart 24 is the ideal solution for climates requiring a high level of solar control, but not the thermal insulation provided by double glazing. Its silver coating delivers powerful solar control. And since it has to be laminated (with the PVB glued to the coating), it also provides a high level of safety.

The first Stopray coating specially developed for use in laminated versions!

LAMISMART 24

Characteristics ...

How you benefit!

Very low solar factor (SF = 25%) – Maintain pleasant indoor temperatures while reducing air conditioning costs

The coating, which the PVB must be glued onto, does not require edge-deletion* – Massively facilitate your glass processing

Stopray LamiSmart 24 can also be toughened prior to lamination – Stock just one product! The toughened and non-toughened versions deliver the same energy and light performance

The metallic blue colour can have different visual nuances – Choose the appearance you want by laminating it with a clear or coloured glass (Green, Bronze, Grey, Dark Blue)

The coating has a high level of chemical resistance – Keep the product in stock for up to 9 months (for unprotected sheets) or 12 months (for sheets protected by desiccant and tape)

Monolithic version, Stopray LamiSmart 24 – Boost the efficiency of your production facilities by laminating the glass yourself!

Laminated version (44.1), Stratobel Stopray LamiSmart 24 – Opt for ease and speed, combined with AGC assembly quality

* Please follow the processing instructions set out in the "Stopray Smart Processing Guide" and in the "Stopray Smart - Sealant Compatibility Structural Glazing Guide". Do not hesitate to contact your AGC representative.