

PLANIBEL LOW-E *Thermal insulation, neutral aesthetics and high light transmission*

Double Glazing 6-16-4 (with 100% air)

	Position	Colour	LT EN 410	SF EN 410	LR EN 410	EA EN 410	SC EN 410	U _g VAL ⁽¹⁾ EN 673	Tempe- rable	Bendable	Silkscreen printing	Edge deletion	Shelf life
TOP N+	# 2	Neutral	78	54	13	24	0.62	1.4	No	No	No	Yes	3 months
TOP N+T	# 2	Neutral	79	58	14	23	0.67	1.4	Yes	Yes	Yes	Yes	3 months
ENERGY N	# 2	Neutral	70	41	12	34	0.47	1.4	No	No	No	Yes	3 months
ENERGY NT	# 2	Neutral	74	44	13	30	0.51	1.3	Yes	Yes	Yes	Yes	3 months
PLANIBEL G	# 2	Neutral	73	64	16	28	0.74	1.7	Yes	Yes	Yes	No	Unlimited
PLANIBEL G FAST	# 2 ⁽²⁾	Neutral	74	65	17	25	0.75	1.7	Yes	Yes	Yes	No	Unlimited

SUNERGY *Neutral, hard-coated glass offering solar protection and good thermal insulation*

Double Glazing 6-16-4 (with 100% air)

	Coating Position	Colour	LT EN 410	SF EN 410	LR EN 410	EA EN 410	SC EN 410	U _g VAL ⁽¹⁾ EN 673	Tempe- rable	Bendable	Silkscreen printing	Edge deletion	Shelf life
SUNERGY CLEAR	# 2	Neutral	61	52	12	42	0.60	2.0	Yes	Yes	Yes	No	Unlimited
SUNERGY GREEN	# 2	Green	51	34	10	66	0.39	2.0	Yes	Yes	Yes	No	Unlimited
SUNERGY AZUR	# 2	Light Blue	50	36	10	62	0.41	2.0	Yes	Yes	Yes	No	Unlimited
SUNERGY DARK BLUE	# 2	Dark Blue	37	30	8	71	0.34	2.0	Yes	Yes	Yes	No	Unlimited
SUNERGY GREY	# 2	Grey	30	33	6	67	0.38	2.0	Yes	Yes	Yes	No	Unlimited

STOPSOL *Reflective, hard-coated glass providing solar control*

Double Glazing 6-16-4 (with 100% air)

	Coating Position	Colour	LT EN 410	SF EN 410	LR EN 410	EA EN 410	SC EN 410	U _g VAL ⁽¹⁾ EN 673	Tempe- rable	Bendable	Silkscreen printing	Edge deletion	Shelf life
CLASSIC CLEAR	# 2	Neutral	35	46	28	37	0.53	2.7	Yes	Yes	Yes	No	Unlimited
CLASSIC GREY	# 2	Grey	17	32	10	67	0.37	2.7	Yes	Yes	Yes	No	Unlimited
CLASSIC GREEN	# 2	Green	29	28	20	70	0.32	2.7	Yes	Yes	Yes	No	Unlimited
CLASSIC BRONZE	# 2	Bronze	20	34	12	64	0.39	2.7	Yes	Yes	Yes	No	Unlimited
CLASSIC DARK BLUE	# 2	Dark Blue	22	27	14	72	0.31	2.7	Yes	Yes	Yes	No	Unlimited
SUPERSILVER CLEAR	# 2	Neutral	58	60	38	18	0.69	2.7	Yes	Yes	Yes	No	Unlimited
SUPERSILVER GREY	# 2	Grey	27	38	12	60	0.44	2.7	Yes	Yes	Yes	No	Unlimited
SUPERSILVER GREEN	# 2	Green	48	37	27	56	0.43	2.7	Yes	Yes	Yes	No	Unlimited
SUPERSILVER DARK BLUE	# 2	Dark Blue	38	35	19	60	0.40	2.7	Yes	Yes	Yes	No	Unlimited
SILVERLIGHT PRIVABLUE	# 2	Intense Blue	25	24	8	79	0.28	2.7	Yes	Yes	Yes	No	Unlimited

⁽¹⁾ Identical values for a 15 or 16 mm spacer

⁽²⁾ Only 4-16-4

EVOLUTION

AGC

COATING

STOPRAY *Soft-coated single glazing offering thermal insulation and maximum solar protection*

Double Glazing 6-16-4 (with 100% air)

	Coating Position	Colour	LT EN 410	SF EN 410	LR EN 410	EA EN 410	SC EN 410	U _g VAL ⁽¹⁾ EN 673	Tempe- rable	Bendable	Silkscreen printing	Edge deletion	Shelf life
STOPRAY ELITE	# 2	Neutral	67	40	14	33	0.46	1.4	No	No	No	Yes	3 months
STOPRAY SAFIR	# 2	Neutral	61	35	15	36	0.40	1.4	No	No	No	Yes	3 months
STOPRAY VISION-60T	# 2	Neutral	60	38	14	38	0.44	1.4	Yes	Yes	Yes	Yes	3 months
STOPRAY VISION-50	# 2	Neutral	50	29	19	42	0.33	1.3	No	No	No	Yes	3 months
STOPRAY VISION-50T	# 2	Neutral	50	32	20	37	0.37	1.4	Yes	Yes	Yes	Yes	3 months
STOPRAY SILVER	# 2	Neutral	43	27	47	27	0.31	1.4	No	No	No	Yes	3 months
STOPRAY GALAXY ON CLEARVISION	# 2	Neutral	41	22	17	43	0.25	1.4	No	No	No	Yes	3 months
STOPRAY LIME 61T	# 2	Green	61	33	10	63	0.38	1.3	Yes	Yes	Yes	Yes	3 months
STOPRAY TITANIUM 37T	# 2	Grey	37	27	6	64	0.31	1.3	Yes	Yes	Yes	Yes	3 months
STOPRAY INDIGO 48T	# 2	Dark Blue	48	29	8	66	0.33	1.3	Yes	Yes	Yes	Yes	3 months

⁽¹⁾ Identical values for a 15 or 16 mm spacer